

REPORT DOCUMENTATION PAGEForm Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.**

1. REPORT DATE (DD-MM-YYYY)

6 May 2003

2. REPORT TYPE

Technical Abstract

3. DATES COVERED (From - To)**4. TITLE AND SUBTITLE**

The Effect of Pressure and Acoustic Excitation on Coaxial LN2/GN2 Jets

5a. CONTRACT NUMBER**5b. GRANT NUMBER****5c. PROGRAM ELEMENT NUMBER****6. AUTHOR(S)**

D. Davis, B. Cherhoudi, D. Talley

5d. PROJECT NUMBER

2308

5e. TASK NUMBER

M13C

5f. WORK UNIT NUMBER**7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)**ERC, Inc.
10 E. Saturn Blvd.
Edwards AFB CA 93524-7680**8. PERFORMING ORGANIZATION REPORT NUMBER**

AFRL-PR-ED-AB-2003-124

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)Air Force Research Laboratory (AFMC)
AFRL/PRS
5 Pollux Drive
Edwards AFB CA 93524-7048**10. SPONSOR/MONITOR'S ACRONYM(S)****11. SPONSOR/MONITOR'S NUMBER(S)**

AFRL-PR-ED-AB-2003-124

12. DISTRIBUTION / AVAILABILITY STATEMENT

Approved for public release; distribution unlimited.

13. SUPPLEMENTARY NOTES**14. ABSTRACT**

20030606 106

15. SUBJECT TERMS**16. SECURITY CLASSIFICATION OF:****17. LIMITATION OF ABSTRACT****18. NUMBER OF PAGES****19a. NAME OF RESPONSIBLE PERSON**
Sheila Benner**a. REPORT****b. ABSTRACT****c. THIS PAGE**

Unclassified

Unclassified

Unclassified

A

19b. TELEPHONE NUMBER (include area code)
(661) 275-5693Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std. Z39.18

Best Available Copy

The Effect of Pressure and Acoustic Excitation on Coaxial LN₂/GN₂ Jets

Davis, D., Chehroudi, B., and Talley, D.

The present trend in liquid rocket engines, gas turbines, and Diesel engines, is towards increasingly higher chamber pressures. In many cases, the chamber pressure can exceed the critical pressures of the fuel or oxidant. Above the critical pressure, the distinction between the gas and liquid phases is lost, and mechanisms conventionally associated with subcritical spray combustion no longer necessarily apply. Until recently, relatively little has been understood about the injection and combustion behavior of propellants at supercritical chamber pressures. The results presented here are an extension of our previous work [1,2] systematically investigating liquid rocket injector behavior at subcritical and supercritical pressures. The injector for this work is a coaxial injector, with the center post being identical to that used in previous single round jet studies [1,2]. In this way, departures from single round jet behavior can be systematically explored. The center post of the coaxial injector has an inner diameter of 0.5 mm and an outer diameter of approximately 1.6 mm. The annulus gap is approximately 0.7 mm. The fluid issuing from the center post of the injector was liquid nitrogen (LN₂) at about 100K. Slightly warmer (~140K – 170K) and less dense ($\rho_L/\rho_g \sim 5-15$) gaseous nitrogen (GN₂) flowed from the annulus. The chamber was pressurized with GN₂ at ambient temperature. The effects of selected parameters are investigated, including the gas-to-liquid velocity ratio, mass flow rate ratio, different coaxial gases, and some geometrical parameters.

Preliminary calculations of the key operating parameters shows that velocity ratios (u_g/u_L) of the order of 10 and momentum flux ratios ($\rho_g u_g^2 / \rho_L u_L^2$) of about 3.5 are achievable using the present experiment. These values are similar to those of practical devices such as the Space Shuttle Main Engine (SSME) preburner, where $\rho_g u_g^2 / \rho_L u_L^2 \sim 3.45$ and $u_g/u_L \sim 10$ [3]. The coaxial jets are exposed to an acoustic field generated via a specially-designed piezo-siren, as described in refs. [2,4], capable of producing acoustical amplitudes of 180dB, with the strongest chamber resonances at 2.7 and 4.8 kHz. Thus the coupling of acoustic waves with jet process can be studied, having relevance to combustion instabilities in liquid rocket engines. Previous studies of acoustically excited single round jets with no coaxial gas flow [2] showed that at supercritical pressures the jet was relatively unaffected by the acoustic waves. However, more recent results where the coaxial gas flow was added [4] showed that the jets interacted with the acoustic waves even at supercritical pressures.

The principle diagnostic for this work is shadowgraph imaging using a model K2 Infinity long distance microscope fitted to a high resolution CCD camera by the Cooke Corporation. However, in addition to the shadowgraph data, preliminary laser-induced thermal acoustics (LITA) measurements are also presented. The LITA measurements provide a quantifiable measurement of the local speed of sound which can be related to temperature and density variations within the flow. Quantitative measurements have been made in the past [5] using a Raman technique, producing Raman intensities which are theoretically related to the density profiles. Representative results showing markedly different intensity profiles at subcritical and supercritical pressures are reproduced in Fig. 1. However, significant uncertainties in the Raman cross-section exist in the

supercritical regime. The LITA approach is an alternative technique which is expected to reduce the uncertainties associated with Raman measurements.

References

1. Chehroudi, B., Cohn, R., and Talley, D.G., "Cryogenic Shear Layers: Experiments and Phenomenological Modeling of the Initial Growth Rate Under Subcritical and Supercritical Conditions," *International Journal of Heat and Fluid Flow*, vol. 23, pp. 554-563 (2002).
2. Chehroudi, B. and Talley, D. "Interaction of Acoustic Waves with a Cryogenic Nitrogen Jet at Sub- and Supercritical Pressures," 40th AIAA Aerospace Sciences Meeting and Exhibit, paper AIAA 2002-0342, Reno, NV, 14-17 January, 2002.
3. Strakey, P.A., Talley, D.G., and Hutt, J.J., "Mixing Characteristics of Coaxial Injectors at High Gas to Liquid Momentum Ratios," *Journal of Propulsion and Power*, vol. 17, no. 2, March-April (2001).
4. Chehroudi, B., Davis, D., and Talley, D., "Initial Results From A Cryogenic Coaxial Injector In An Acoustic Field," 41th AIAA Aerospace Sciences Meeting and Exhibit, paper AIAA 2003-1339, Reno, NV, 6-9 January 2002.
5. Chehroudi, B., Cohn, R., Talley, D., and Badakhshan, A., "Raman Scattering Measurements in the Initial Region of Sub- and Supercritical Jets," 36th AIAA/ASME/SAE/ASEE Joint Propulsion Conference, paper AIAA-2000-3392, Huntsville, AL, 17-19 July, 2000.




Figure 1. 40-frame-averaged Raman relative intensity radial profiles at two different axial distances from the injector and at sub- and supercritical chamber conditions. X and D are axial distance from the injector exit plane and injector hole diameter, respectively. I_{ch} stands for measured intensity sufficiently far from the jet location. The laser sheet propagation direction is from right to left. Pr is the reduced pressure, chamber pressure/critical pressure of N_2 . [5]